Uni-5 Series

PRICE COMPUTING SCALE with PRINTER and COLOR TOUCHSCREEN





PRICE COMPUTING SCALE with PRINTER and COLOR TOUCHSCREEN





Value by design

Ishida's Uni-5 Series of price-computing scales and printers are one of the best values in retail weighing today. Retail customers may choose from three distinct printer and scale-base configurations—all with the same easy-to-use universal control panel.

Whether selecting the straightforward bench model, bench with pole, or elevated head style, Uni-5 users can appreciate a large, full-color touchscreen, while customers view advertised specials and details of their purchase on an ultra-bright customer-side LCD.

The Uni-5 is more than just attractively priced. It's also attractive in design, with a polished, black polymer housing that's easy to clean, and a convenient side-loading printer for quick label changing. A low-profile design and green energy consumption round out a long list of essential features for today's progressive retail marketplace.

Elevated keyboard and displays model

Standard Features

- Large color touchscreen
- Dual-range weighing
- Side-load labels
- Internal wireless communications
- Ethernet communications
- Up to 99 pages of speed keys
- Adjustable touchscreen viewing angle
- 77 tactile keys
- 4 MB of memory
- Grayscale LCD customer-side display
- 30+ selectable fixed bar code formats
- Compatible with third-party communication software, including Invatron's PLUM, ADC's InterScale and Droste's PCScale Manager







Ontions/Accessories

- ScaleLink Pro 5 scale management software, including label design, data back-up and remote diagnostics
- Seafood and produce platters

Specifications

Capacity: 0-15 lb x 0.005 lb/15-30 lb x 0.01 lb (dual range)

Display: Operator: Color LCD, 7 in

Customer: Grayscale LCD, 7 in

Display Items: Tare: Four-digits

Unit price: Six-digits Weight: Five-digits Total price: Six-digits

Preset Keys: 1980: 20 x 99 pages

Memory Capacity: 4ME

Communications: Static TCP/IP 10/100 Base T Ethernet

Wireless WEP/WPA/WPA2

 Interface:
 USB port, back-up and restore only

 Platter:
 15.7 in x 10.8 in (398 x 275 mm)

 Print Head:
 Direct thermal 2.2 in head (56 mm)

Print Speed: 3.2 /3.9 /4.7 /5.9 in/sec (80 /100 /120 /150 mm/sec)

Label Size: Width: 1.5-2.5 in (38-64 mm)

Label Roll: Length: 1.5-7.9in (38-200mm)

Label Roll: Inside diameter: 1.6in (40mm) min

Outside diameter: 3.9in (100mm) max

 Label Backing Paper:
 Width: Up to 2.6 in (66 mm)

 Power Supply:
 AC100-240V, 50/60 Hz

 Power Consumption:
 Stand-by: 50W,

In operation: 120W

Classification: NTEP CC 07-099A2, UL listed

Warranty: One-year limited warranty











Specifications subject to change without notice.